

WSS7201

Product technical specification

WSS-7201 is used in the formulation of water-based substrate wetting agents, also suitable for radiation curing wetting agents, and also suitable for solvent-based wetting agents and solvent-free wetting agents (two-component) formulations . Especially suitable for automotive paint wetting agent, industrial coating wetting agent, architectural coating substrate wetting agent, decorative coating substrate wetting agent.

- Used for water-based formulations and also suitable for radiation curing formulations
- It is also suitable for solvent-based and solvent-free (two-component) formulations
- Excellent anti-shrinkage effect
- Good recoatability
- Additional flow promotion effect

Recommended Applications

- Car paint
Recommended amount
As supplied calculated on total formulation: 0.05 to 1.0%
- industrial industry coating material
Recommended amount
Based on the supply form to the total formula: 0.1-1.0%
- Decorative paint
Recommended amount
Based on the total formula in the form of supply: 0.2-1.0%
- Inkjet ink
Recommended amount
Based on the supply form to the total formula: 0.1-1.0%
- Leather pre-coating primer primer and top coat based on polyurethane acrylic resin nitro and casein system
Recommended amount
Based on the total formula in the form of supply: 0.2-1.0%

Technical data

- Appearance : transparent liquid
- Active matter content : 100%

chemical composition

Organosiloxane copolymer

Process Description

Pre-diluted or directly added to the paint in the form of supply

package

- 25 kg , plastic drum
- 200 kg , iron drum

Storage stability

Store in unopened original packaging and use within 12 months from the date of production .

Free samples or detail:

Please contact: 006598831607 (Singapore) Mr. Yang